Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources							
Supplier's name or trade mark: Lupus							
Supplier's address: Utveckling, Tallbacksgatan 11R, 19572 Rosersberg, SE							
Model identifie	r: LM4-LUP2-27	(9					
Type of light so	urce:						
Lighting technology used:		LED	Non-directional or directional:	NDLS			
Light source cap-type (or other electric interface)		2-pin connector					
Mains or non-mains:		NMLS	Connected light source (CLS):	Nej			
Colour-tuneable light source:		Nej	Envelope:	-			
High luminance light source:		Ja					
Anti-glare shield:		Nej	Dimmable:	Only with specific dimmers			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		8	Energy efficiency class	F			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		760 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000			
On-mode power (P _{on}), expressed in W		8,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90			
Outer	Height	8	Spectral power	See image			
dimensions	Width	250	distribution in the	in last page			

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	11	range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-			
			Chromaticity	0,434			
			coordinates (x and y)	0,403			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		50	Survival factor	1,00			
the lumen maintenance factor		0,98					

(a)'-': not applicable;

(b)'-': not applicable;

NORMALIZED SPECTRUM

